

Product data sheet Characteristics

438-TR SOCKET CORD EXTENSION 0.75X1SQ FLEXIBLE 250V



Main Range of product Standard Series Product or component Socket-outlet type Colour Transparent Product brand Clipsal Quantity per set Set of 1 Cover type Complete housing

Complementary

Marking Without marking Local signalling Without light indicator Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm Diameter 43 mm	Colour code	TR	
Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Marking	Without marking	
[In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Local signalling	Without light indicator	
[Ue] rated operational voltage 250 V AC Depth 71 mm	Material	PVC (polyvinyl chloride)	
Depth 71 mm	[In] rated current	10 A	
<u>'</u>	[Ue] rated operational voltage	250 V AC	
Diameter 43 mm	Depth	71 mm	
	Diameter	43 mm	

Environment

AS/NZS 3112	
AS 3100	
AS 3109	
AS/NZS 3122:approval number S/1	
	AS 3100 AS 3109

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	0.057 kg	
Package 1 Height	7.2 cm	
Package 1 width	5 cm	
Package 1 Length	5 cm	