

### Product data sheet Characteristics

# O3025-XW

## Switched socket outlet, Iconic Outdoor, horizontal, Twin, 10 A, 250 V, Extra white



Main	
Range of product	Iconic
Product or component type	Switched socket
Product brand	Clipsal
Device presentation	Complete product
Colour	White
Colour code	XW
Switch application	On/off switching
Outlet poles configuration	1P + E

#### Complementary

Control type	ON/OFF button Rocker
Pin number	6
Number of power socket outlets	2
Socket-outlet type	Twin switched socket-outlet
Fixing mode	By screws By clipping locks
Local signalling	Without light indicator
Device mounting	Surface Wall mounted
Mounting position	Horizontal
Material	PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Surface finish	Matt
Type of installation	Outdoor
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
[In] rated current	10 A
Clamping connection capacity	4 x 2.5 mm <sup>2</sup> 3 x 4 mm <sup>2</sup>
Connections - terminals	3 screw terminals
Depth	70 mm
Height	85 mm
Width	115.5 mm

#### Environment

IP degree of protection	IP54	
Product certifications	RCM	
Electrical durability	12000 cycles	
Ambient air temperature for storage	060 °C	
Standards	AS/NZS 3112	
Relative humidity	1095 %	
Ambient air temperature for operation	045 °C	

### Offer Sustainability

REACh Regulation	<sup>™</sup> REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€ Yes	
China RoHS Regulation	China RoHS Declaration	
Halogen content performance	Halogen free plastic parts product	

Life Is On