II CLIPSAL



Double switched socket outlet, Clipsal Solis T Series, horizontal, 10A, brushed brass

1025XUA-BB

Main

Range	Clipsal Solis T Series
Product or component type	Switched socket
Product brand	Clipsal
Assembly Type	Complete product
Colour tint	Brushed brass
Protection	Shuttered
Main colour tint	Brushed brass

Complementary

,		
control type	Rocker	
Number Of Outlets	2	
Socket-outlet type	Double socket-outlet	
Mounting Type	Screw	
Installation Type	Flush	
Installation Orientation	Horizontal	
Material	Aluminium	
Surface finish	Metallic	
[Ue] rated operational voltage	230/240 V AC	
Network frequency	50 Hz	
[In] rated current	10 A	
Connections - terminals	4 x 2.5 mm² screw terminals 3 x 4 mm² screw terminals	
Embedding depth	23.5 mm	
Depth	27.4 mm	
Height	74 mm	
Width	148 mm	
Mounting Centers	120 mm	
Cut-out dimensions	130 x 50 mm	
surface treatment	Anodised	
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)	
Wire stripping length	16 mm	

Number of power socket outlets	2 x 2P + E, Australian/New Zealand	
Cover Thickness	3.9 mm	
Number Of Switches	2	

Environment

Product certifications	RCM
Standards	AS/NZS 3112
Relative humidity	1095 %
Ambient air temperature for operation	045 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	6 cm
Package 1 Length	8 cm
Package 1 Weight	176 g
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	32.5 cm
Package 2 Width	25 cm
Package 2 Length	41 cm
Package 2 Weight	7.42 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	2
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No

1025XUA-BB

Image of product / Alternate images

Alternative













