

Product data sheet

Characteristics

1439/20-TR

PLUG TOP 20A 250V 3 PIN



Main

| | |
|------------------|-----------------|
| Range of product | Standard Series |
| Product brand | Clipsal |





Complementary

| | |
|-------------------------------------|---|
| [In] rated current | 20 A |
| [Ue] rated operational voltage | 230 V 50/60 Hz conforming to EN 60309-2 |
| Colour | Body: transparent |
| Material | Plastic |
| Connections - terminals | Screw terminal |
| Plug, socket, control station shape | Straight |
| Duration | 6 h |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 48 g |
| Package 1 Height | 4.5 cm |
| Package 1 width | 6.8 cm |
| Package 1 Length | 10 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |