

Product data sheet Characteristics

2025VXA-WE SWITCHED SOCKET TWIN VERTICAL 10A **EXTRA SWITCH**





Main	
Range of product	Series 2000
Product or component type	Switched socket
Product brand	Clipsal
Colour	White electric

Complementary

Control typeON/OFF buttonNumber of gangs2 gangsPin number3Number of power socket outlets2ActuatorSwitch RockerFixing modeBy screwsLocal signallingWithout light indicatorMounting positionVerticalMaterialPlasticSurface finishGlossy[Ue] rated operational voltage250 V AC[In] rated current10 ADepth28 mmLength116 mmWidth76 mmFixing center84 mm			
Pin number 3 Number of power socket outlets 2 Actuator Switch Rocker Fixing mode By screws Local signalling Without light indicator Mounting position Vertical Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Control type	ON/OFF button	
Number of power socket outlets 2 Actuator Switch Rocker Fixing mode By screws Local signalling Without light indicator Mounting position Vertical Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Number of gangs	2 gangs	
Actuator Switch Rocker Fixing mode By screws Local signalling Without light indicator Mounting position Vertical Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Pin number	3	
Fixing modeBy screwsLocal signallingWithout light indicatorMounting positionVerticalMaterialPlasticSurface finishGlossy[Ue] rated operational voltage250 V AC[In] rated current10 ADepth28 mmLength116 mmWidth76 mm	Number of power socket outlets	2	
Local signallingWithout light indicatorMounting positionVerticalMaterialPlasticSurface finishGlossy[Ue] rated operational voltage250 V AC[In] rated current10 ADepth28 mmLength116 mmWidth76 mm	Actuator		
Mounting positionVerticalMaterialPlasticSurface finishGlossy[Ue] rated operational voltage250 V AC[In] rated current10 ADepth28 mmLength116 mmWidth76 mm	Fixing mode	By screws	
Material Plastic Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Local signalling	Without light indicator	
Surface finish Glossy [Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Mounting position	Vertical	
[Ue] rated operational voltage 250 V AC [In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Material	Plastic	
[In] rated current 10 A Depth 28 mm Length 116 mm Width 76 mm	Surface finish	Glossy	
Depth 28 mm Length 116 mm Width 76 mm	[Ue] rated operational voltage	250 V AC	
Length 116 mm Width 76 mm	[In] rated current	10 A	
Width 76 mm	Depth	28 mm	
	Length	116 mm	
Fixing center 84 mm	Width	76 mm	
	Fixing center	84 mm	

Environment

Standards	AS/NZS 3100
	AS/NZS 3112
	AS/NZS 3133:approval number S/1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	122 g	
Package 1 Height	31 mm	
Package 1 width	117 mm	
Package 1 Length	189 mm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	

Oct 14, 2021 Life Is On CLIPSAL

1

Package 2 Weight	1.31 kg	
Package 2 Height	128 mm	
Package 2 width	148 mm	
Package 2 Length	166 mm	
Unit Type of Package 3	CAR	
Number of Units in Package 3	100	
Package 3 Weight	13.2 kg	
Package 3 Height	254 mm	
Package 3 width	348 mm	
Package 3 Length	445 mm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant ☐EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Life Is On