

STOCKTON SINGLE DIFFUSED LED BATTEN

Features

- Installation: Surface/series mount, suspended
- Robust wide body design
- Contractor friendly installation
- Precision lock tombstone lamp holders
- Keyhole slot on cover for easy opening
- 16mm² terminal block
- 2 x 25mm cable entry with bush
- Lumen output: 110lm per Watt
- Lifetime: 50 000 Hrs
- Available in emergency

Specifications

Body and End Cap: Steel
 Diffuser: K12 Prismatic
 Screws: Zinc Plated
 Finish: Powder White
 Light Category: LED SMD 2835
 Lamp CCT: 5000K-5500K
 Lamp: Linear T8-G13 Base
 Input Voltage: 250V 50Hz
 LED Driver: Non dimmable
 Operating Temp: -10°C to 45°C
 Operating Humidity: 0-90%
 Ingress Protection: IP20
 Warranty: Two years

Application

Ideal for indoor residential areas, commercial offices and warehousing applications



Part No.	Description	(lm)	Beam °	Length	Width	Height
NLS20332	1x10W LED T8 LINEAR WIDE BODY BATTEN K12	1100lm	150	614mm	70mm	90mm
NLS20351	1x18W LED T8 LINEAR WIDE BODY BATTEN K12	1950lm	150	1224mm	70mm	90mm
NLS20385	1x18W LED T8 LINEAR WIDE BODY BATTEN K12 EMX	1950lm	150	1224mm	70mm	90mm