

SHIELDLUX VANDAL-RESISTANT LED BATTEN

Features

- Installation: Surface mount
- High impact resistant opal diffuser
- Vandal-resistant design
- Dust and water resistant
- High efficiency SMD2835
- CRI: Ra>80
- Average lifetime: 30 000hrs
- Individually boxed in merchandise packaging
- Adjustable power function: 40/38/36/34/32/30/28/26 Watts
- Lumin output: 4400/4200/4000/3800/3600/3400/3200/3000
- Accessory: Screw kit

Specifications

- Base and Diffuser: Polycarbonate
- Screws: 316 Stainless Steel
- Led Chip Type: SMD2835
- Input Voltage: 220-240Vac 50/60Hz
- Power Factor: >0.9
- LED Driver: Non dimmable
- Operating °C: -10°C—45°C
- Operating Humidity: 0-90%
- IP Protection: IP54
- IK Resistance: IK10
- L/U 220-240V 50Hz
- 40w PF>0.9 >4400LM

Application

Perfectly suited for recreational and athletic facilities, commercial warehouses, educational institutions, shopping complexes, public infrastructure, security uses, and residential neighborhoods.



Adjustable lumin output switch



Code	Watts	CCT	Lumen	Length	Width	Height
20370NLS	40W	3000K/4000K/6500K	Up to 4400lm	1285mm	96mm	108mm