



## Main

Range	Clipsal Iconic
Product or component type	Switched socket
Device presentation	Complete product
Outlet poles configuration	2P + E with shutter
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1
Rated current	10 A, 250 V AC, 50 Hz

## Complementary

Device mounting	Flush
Number of power socket outlets	2
Number of rocker	2
Outlet standard	Australian
Outlet standard description	With earthing contact
Outlet standard	Australian/New Zealand
Ground lug position	Straight 180° position
Fixing mode	By screw
Installation direction	Horizontal
Colour tint	Vivid white (VW)
Surface finish	Matt
Ambient air temperature for storage	0...60 °C
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	12000 cycles
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1 x 2.5...4 x 2.5 mm <sup>2</sup> (rigid) 1 x 2.5...4 x 2.5 mm <sup>2</sup> (rigid) 1 x 2.5...4 x 2.5 mm <sup>2</sup> (stranded) 1 x 2.5...4 x 2.5 mm <sup>2</sup> (flexible)
Wire stripping length	16 mm
Material	ABS (acrylonitrile butadiene-styrene) for cover frame POM (polyoxymethylene) for shutter POM (polyoxymethylene) for shutter POM (polyoxymethylene) for locking bar PC (polycarbonate) for fixing frame PP (polypropylene) for rocker PC (polycarbonate) for cover frame
Height	120 mm
Width	78 mm
Depth	44 mm
Standards	AS/NZS 60950-1 AS/NZS 3112

## Environment

## Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.