

Product data sheet Characteristics

30MD-BK

Clipsal - Mechanisms, Switch Mechanisms, 30 Series, 250V 10A - Double Pole, Single Throw





Main

IVIAIII	
Range of product	Series 30 Standard Series
Product brand	Clipsal
Device presentation	Basic element

Complementary

Switch function	2-pole
Number of rocker	1
Number of poles	2
Device mounting	Flush
Material	PVC (polyvinyl chloride)
Surface finish	Glossy
Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	10 A
Load type	Fluorescent lamp 10 A LEDi lamp 100 W
Marking	Without marking
Actuator	Rocker

Packing Units

r acking critis	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 cm
Package 1 Width	2.36 cm
Package 1 Length	2.9 cm
Package 1 Weight	0.014 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	3.4 cm
Package 2 Width	5.2 cm
Package 2 Length	7.3 cm
Package 2 Weight	0.09 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	500
Package 3 Height	22.6 cm
Package 3 Width	19.1 cm

Package 3 Length	35.9 cm
Package 3 Weight	9.2 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	



2