

Product data sheet Characteristics

40MI

Pro Series, switch, 40M, Intermediate, 250 V, 10 A



Main

Mairi	
Range	Pro Series
Product or component type	Switch
Device application	Lighting

Complementary

Device presentation	Mechanism	
Control type	Rocker	
Switch function	Intermediate	
Rated current	10 A	
[Ue] rated operational voltage	250 V	
Fixing mode	By clips	
Surface treatment	Untreated	
Connections - terminals	Screw terminal	
Clamping connection capacity	1 x 1.54 x 1.5 mm ² for rigid or stranded cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s)	
Height	23 mm	
Width	23 mm	

Environment

Environment			
Ambient air temperature for operation	045 °C		
Relative humidity	1095 %		

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	15.98 g	
Package 1 Height	22 mm	
Package 1 width	22 mm	
Package 1 Length	24 mm	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation		
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Life Is On