

Product datasheet

Specifications



Push Button - Momentary, Iconic,
10A, 230/240V, LED, vivid white

40PBBP-VW

Main

Range	Iconic
Product or component type	Bell press switch
Device application	Lighting
Number of rocker	1
Aesthetic name	Iconic
Switch function	1/2-way
Colour tint	Vivid white (VW)
Quantity per set	1 piece

Complementary

Device presentation	Complete product
Device mounting	Embedded
Actuator	Push-button
Switch application	Switch
[Ue] rated operational voltage	230/240 V
Network type	AC
Network frequency	50 Hz
Rated current	10 A
surface treatment	Untreated
Surface finish	Matt
Connections - terminals	Screw terminals
fixing mode	By clipping locks
IP degree of protection	IP3X
Width	22 mm
Height	22 mm
Depth	42 mm
Embedding depth	37 mm

Environment

Standards	AS/NZS 3133
Ambient air temperature for operation	-3...50 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	2.7 cm
Package 1 Length	2.7 cm
Package 1 Weight	24.49 g
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	7 cm
Package 2 Width	11.9 cm
Package 2 Length	14.6 cm
Package 2 Weight	540.11 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	17.5 cm
Package 3 Width	16 cm
Package 3 Length	26 cm
Package 3 Weight	2.307 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	45 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	45 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	38
End of life manual availability	No need of specific recycling operations

Image of product / Alternate images

Alternative







