

Product data sheet Characteristics

41E2PBSWM-VW

Connected Switch, Iconic, BLE default mode, 2 AX, 240 V, Vivid white



Main Range compatibility Clipsal Iconic cover plate Pro Series cover plate Product brand Clipsal Range Iconic Product or component Electronic switch

Complementary

Device presentation	Mechanism	
Load type	Dimmable LED lighting driver: 2 A LED lighting driver (non-dimmable): 2 A Electronic transformer: 2 A Medium voltage halogen lamp: 2 A Linear fluorescent ballast: 2 A Inductive: 2 A (cos phi =0.6) Resistive: 2 A Motor: 2 A	
[Ue] rated operational voltage	220240 V AC 50 Hz	
Protection type	Over temperature protection Thermal protection	
Colour tint	Vivid white (VW)	
Local signalling	LED	
Control type	Push-button By mobile application	
Software name	Wiser by SE App	
Technology type	Bluetooth low energy default Zigbee	
Wiring configuration	3-wire	
Material	Plastic	
Mounting support	Grid	
Device mounting	Flush	
Fixing mode	Clip-in	
Fixing center	84 mm	
Type of installation	Indoor installation	
Embedding depth	40 mm	
Depth	56 mm	
Width	22 mm	
Height	22 mm	

type

Environment

IP degree of protection	IP20	
Relative humidity	590 % non-condensing	
Standards	AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	

Life Is On | IICLIPSAL