Specifications

CLIPSAL



Clipsal - 56 Series, Appliance Inlet, 5 Round PIN, 32A, 500V, IP66

56AI532-GY

Main

Range	Clipsal - 56 Series
Range Of Produc	Series 56
Product Brand	Clipsal
Product Or Component Type	Appliance inlet
Device Application	Power supply

alomontary

Complementary	
[In] Rated Current	32 A
Poles Description	3P + N + E
[Ue] Rated Operational Voltage	500 V 50/60 Hz conforming to EN 60309-2
Colour	Grey (RAL 7035)
Material	Plastic
Plug, Socket Category	Low voltage
Material	Polycarbonate: cover
Mounting Mode	Surface mounted
Outlet Standard	Australian/New Zealand
Outlet Standard	Industrial
Tightening Torque	0.8 N.m
Connections - Terminals	Screw terminal 616 mm ² rigid or stranded cable
Contacts Material	Screws: brass
Plug, Socket, Control Station Shape	Angled
Duration	7 h
Net Weight	0.98 kg
Height	204 mm
Width	101 mm
Depth	165 mm
Targeted Country	Australia

Environment

Standards

Ip Degree Of Protection

IP66 conforming to AS 60529

AS/NZS 60320.1

Ambient Air Temperature For -25...75 °C Operation

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.6 cm
Package 1 Width	10.2 cm
Package 1 Length	20.1 cm
Package 1 Weight	978.0 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information