

## Product data sheet Characteristics

# 56C320F-GY

Clipsal - 56 Series, Switched Socket Outlet, 250V, 20A, 3 Flat PIN, IP66, 1 Pole



## Main

IVIAIII	
Range of produc	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Grey (RAL 7035)

#### Complementary

Number of poles	3	
Plug, socket category	Low voltage	
Outlet standard	Australian/New Zealand	
Plug, socket, control station shape	Straight	_
Number of modules	1	_
Number of power socket outlets	1 protective cover	_
[In] rated current	20 A	_
[Ue] rated operational voltage	250 V AC 50 Hz	
Poles description	1P + N + E	
Protection type	Without protection	
Device mounting	Surface	
Material	Polycarbonate: cover	
Contacts material	Pins: phosphor bronze	
Connections - terminals	Screw terminals cable(s) 2.56 mm²	
Electrical connection	Industrial connector	
Depth	108 mm	
Width	101 mm	
Height	204 mm	
Targeted country	Australia	

#### Environment

Standards	AS/NZS 3123 AS/NZS 3133
Ambient air temperature for operation	-2575 °C
IP degree of protection	IP66 conforming to AS 60529

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	11.35 cm	
Package 1 Width	10.35 cm	
Package 1 Length	20.65 cm	
Package 1 Weight	944.0 g	

#### Offer Sustainability

REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	

Life Is On