

## Product data sheet Characteristics

# 5750WPL-GY

# C-Bus Control and Management System, Passive Infrared Sensor, 110deg





#### Main Range C-Bus Clipsal Product brand Product or component Occupancy sensor type Device application Lighting Sensor type PIR Product specific Staircase monitoring

Grey

#### Complementary

[Ue] rated operational voltage	1536 V DC
[ln] rated current	18 mA
Communication network type	C-Bus 100
Number of channels	1
Type of setting	Light sensitivity adjustable
Light intensity adjustment	1 lux user selectable
Data backed up	Non-volatile memory
Local signalling	LED for status
Timer resolution	1 s
Warm-up time	5 s
Horizontal detection angle	0110 °
Time delay range	01 s (switch-on)
Duty cycle	1090 min
Detection face	Lateral: 12 m Frontal: 18 m
C Bus termination	2 flying leads
Material	Plastic
Device mounting	Surface
Mounting support	Wall Ceiling
Mounting height	2.4 m
Fixing center	84 mm
Width	74 mm
Height	111 mm
Depth	138 mm
Colour code	GY

application

Colour

#### Environment

IP degree of protection	IP66
Ambient air temperature for operation	045 °C

### Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.6 cm
Package 1 Width	17.6 cm
Package 1 Length	24.8 cm
Package 1 Weight	340 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	18.2 cm
Package 2 Width	30.8 cm
Package 2 Length	45.3 cm
Package 2 Weight	3.6 kg

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Life Is On