

National Light Sources Pty Ltd

www.nslight.com.au

Features

- Certified to AS/NZS3112, AS/NZS3123, AS/NZS3133, AS/NZS3100, AS/NZS3947.3
- IP66 rating prevents water and dust ingress
- Large cable terminals with internal wiring for easy installation
- Made from impact resistant plastic materials for guaranteed long life after installation
- Facility for padlocking both, the rotary switch, and the transparent cover of RCD enclosure
- Rated Voltage: 250V/500V AC
- Rated Frequency: 50/60Hz
- Utilisation category: AC22A

IMPORTANT - Must be installed:

To manufacturers specification and by a qualified licensed electrician



Part No.	Description	Rating	Phases	Voltage
NLS30643	3 Flat Pins 10A Combination Outlet + 2 Pole 25A RCD	10A	1	250V
NLS30644	3 Flat Pins 15A Combination Outlet + 2 Pole 25A RCD	15A	1	250V
NLS30645	3 Round Pins 32A Combination Outlet + 2 Pole 40A RCD	32A	1	250V
NLS30646	4 Round Pins 20A Combination Outlet + 2 Pole 25A RCD	20A	3	500V
NLS30647	4 Round Pins 32A Combination Outlet + 2 Pole 40A RCD	32A	3	500V
NLS30648	5 Round Pins 20A Combination Outlet + 2 Pole 25A RCD	20A	3	500V
NLS30649	5 Round Pins 32A Combination Outlet + 2 Pole 40A RCD	32A	3	500V
NLS30651	Quad Back Plate with Inserts	N/A	N/A	N/A