

Product data sheet Characteristics

7006A FAN EXH WALL 150MM-AUTO LOUVRE





Main

| Product brand | Clipsal |
|---------------|---------|
|---------------|---------|

Complementary

| [Ue] rated operational voltage | 230240 V AC | |
|--------------------------------|------------------|--|
| Air flow | 360 m3/h | |
| Diameter | 148 mm impeller: | |
| Power consumption in W | 45 W | |
| [In] rated current | 0.27 A full load | |

Environment

| IP degree of protection | IPx4 |
|-------------------------|------|
|-------------------------|------|

Packing Units

| 1945.000 g | |
|------------|--------------------------|
| 210.000 mm | |
| 250.000 mm | |
| 250.000 mm | |
| - | 210.000 mm 250.000 mm |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--------------------------------|--|
| REACh Regulation | [™] REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EEU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | ₽¥Yes | |
| China RoHS Regulation | China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |
| | | |