

## Product data sheet

### Characteristics

# 7600LEDLAMP

LED downlight, Airflow, 8W, 230/240V, 600lm, 3000K, white



### Main

Range	Airflow
Product or component type	Downlight
Device application	Lighting
Market segment	Residential
Main colour tint	White
Colour tint	White

### Complementary

Device mounting	Recessed ceiling
Rated power in W	8 W
Light source	LED
Total system power	230/240 V AC 50 Hz
Luminous flux	600 lm 3000 K warm white
Colour rendering index	R <sub>a</sub> =80
Load type	230 V AC LED lamp
Trim width	150 mm
Trim height	55 mm

### Environment

Unified glare rating	< 22
----------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12 cm
Package 1 Width	6.5 cm
Package 1 Length	6.5 cm
Package 1 Weight	58.3 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	12.8 cm
Package 2 Width	33 cm
Package 2 Length	65.5 cm
Package 2 Weight	3.915 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	1400
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	124.62 kg

## Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>