

## Product data sheet Characteristics

# 9020TCM10-GY

## conduit corrugated turbo pvc medium duty 20mm / 10m





#### Main

Colour	Grey
Product brand	Clipsal

### Complementary

Colour code	GY
Material	PVC (polyvinyl chloride)
Stub stiffness	Flexible
Diameter	Internal: 13.9 mm
External diameter	20 mm

#### **Environment**

Environmental characteristic	Conforming to AS/NZS 61386
Ambient air temperature for operation	-1560 °C

### **Packing Units**

PCE	
1	
707 g	
36 cm	
10 cm	
36 cm	
	1 707 g 36 cm 10 cm

#### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.