



Similar image
(Picture shows ADA910T)

RCBO 1P+N 6kA C-20A 30mA A Class

Architecture

Neutral position	right
Number of protected poles	1
Number of poles	2 P
Type of pole	1P+N
Curve	C

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Connectivity

Top connection alignment for modular devices	Aligned terminal
--	------------------

Main electrical features

Frequency	50 Hz
Rated short circuit breaking capacity I _{cn} AC according IEC60898-1	6 kA
Rated operational voltage U _e	240 V

Voltage

Rated insulation voltage	500 V
Max operating voltage	240 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	30 mA
Withstand not tripping on 8-20 μs wave	250 A
Rated short circuit breaking capacity I _{cn} under 230V AC according IEC60898-1	6 kA
Rated ultimate short-circuit breaking capacity I _{cu} under 230V AC IEC 60947-2	6 kA
Rated ultimate short-circuit breaking capacity I _{cu} under 240V AC IEC 60947-2	6 kA
Breaking and opening capacity	6 kA
Magnetic regulating current at 40° C	5/10 I _n

Technical Properties

min/maxi threshold value of the AC thermal operation 1,13/1,45 In

Electric current / temperature

Rating current -15°C	22,2 A
Rating current -20°C	22,5 A
Rating current 0°C	21,5 A
Rating current 10°C	21 A
Rating current -10°C	22 A
Rating current 15°C	20,8 A
Rating current 20°C	20,5 A
Rating current 25°C	20,3 A
Rating current -25°C	22,7 A
Rating current 30°C	20 A
Rating current 35°C	19,8 A
Rating current 40°C	19,6 A
Rating current 45°C	19,4 A
Rating current 5°C	21,3 A
Rating current -5°C	21,8 A
Rating current 50°C	19,2 A
Rating current 55°C	19 A
Rating current 60°C	18,8 A
Rating current 70°C	13,6 A

Current correction factors

Correction factor of rating current for 2 devices placed 1 side-by-side

Correction factor of rating current for 3 devices placed 0,95 side-by-side

Correction factor of rating current for 4 and 5 devices 0,9 placed side-by-side

Correction factor of rating current for 6 devices placed 0,85 side-by-side

Selectivity

Minimal rating current of upstream aM fuse for selectivity on short-circuit 25 A

Minimal rating current of upstream gL fuse for selectivity on short-circuit 32 A

Maximal rating current of downstream aM fuse for selectivity on short-circuit 4 A

Maximal rating current of downstream gL fuse for selectivity on short-circuit 12 A

Power

Power loss per pole at In 4,8 W

Total power loss under IN 6,6 W

Tripping

Protected against nuisance tripping no

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm

Installation, mounting

Tightening torque	2,1Nm
Type of bottom rail clip for modular devices	plastic
Bottom removability for modular devices	yes
Top removability for modular devices	no

Connection

Connection cross-section at output with screw, for flexible conductor	1/16 mm ²
Connection cross-section of the access with screws, with flexible conductor	1/16 mm ²
Connection cross-section at output with screw, for massive conductor	1/25 mm ²
Connection cross-section for rigid conductor, upstream terminals with screws	1/25 mm ²
Connection cross-sect. rigid cable	1 / 25mm ²
Connection cross-sect. flexible conductor	1 / 16mm ²
Type of connection	with screw

Standards

Standard text	IEC 61009-1, AS/NZS 61009-1
European directive WEEE	not concerned

Safety

Protection index IP	IP20
Residual current type	A

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-25 40 °C
Class of energy limitation I ² t	3
Altitude	2000 m
Storage temperature	-25 to 70 °C
Air humidity protection	for all climates
Storage/transport temperature	-25 70 °C

temperatur

Temperature of calibration	30 °C
----------------------------	-------