

## Product data sheet

### Characteristics

# CLITPDB2

LED diffused batten, Clipsal, 40W, 4000 K,  
4000 lm, white

### Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting

### Complementary

Type of installation	Indoor/outdoor
Total system power	40 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Luminous flux	4000 lm
Bulb lifespan	30000 h
Colour	White
Colour temperature	4000 K
Mounting mode	Ceiling
IP degree of protection	IP20
Electrical insulation class	Class I
Length	1170 mm
Width	72 mm
Height	72.5 mm
Shape	Rectangular
Net weight	1.8 kg

### Environment

Colour rendering index	R <sub>a</sub> =80
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 %

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.