

# NYLON CABLE TIE 300 X 4.8MM NATURAL

Part Number: CT290NT



## Features

- Head and pawl are integrally moulded for added strength and durability. Tip designed for easier pick up, insertion and pull through
- Smooth round edges do not cut insulation
- Self-locking low profile head conserves space
- Not suitable for outdoor use

## Product Description

Strength, durability and adjustability are paramount in the design and development of our cable ties. CABAC nylon cable ties are made from halogen free PA66 nylon with an integrally moulded head and pawl. This, combined with intimate locking engagement between the pawl and strap teeth, means that our cable ties have high durability and strength without any metal parts.

CABAC cable ties are designed to meet applicable strength requirements without sacrificing ease of use. In fact, our cable tie design incorporates several measures to improve comfort and safety. The product has smooth, round edges that are more comfortable to work with and reduce the risk of cuts to cable insulation or hands. The tail of the tie features a bent-tip with v-shaped grooving that prevents your grip from slipping. This means less effort during pick-up,

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

insertion and pull through.

Our natural nylon cable ties are only suitable for indoor applications.

## Technical Data

Loop Tensile Strength: 22kg

Bundle Diameter: 76mm

Length: 300mm

Width: 4.8mm

Thickness: 1.4mm

Colour: Natural

Conformant Standards: UL, Mil Spec, IEC, VDE, DIN.

Refer: Mil-S-23190E - testing

Smoke Emission: Low smoke/ halogen free

Material: PA66

Breakdown Voltage: 20 kV/mm

Moisture Content: 2.5% w.v. @ 23%/50%RH

Operating Temperature: -40 to 85 degrees Celsius

Flammability: Passed U.L. 94V-2

## Tools & Accessories

Installation tools are not required, but suggested where controlled, uniform tension and cut-off are needed.

Cable Tie Tensioning Tool

Part number: KTT

Self-Adhesive Mount

Part number: SAM25NT

Screw Mount

Part number: CTB5NT

## Additional Information

### IMH Resolution MEPC

[Download IMH Resolution MEPC](#)

### ROHS

[Download ROHS](#)

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.