

NYLON CABLE TIE HEAVY DUTY 370X7.6MM UV

Part Number: CT365BK-HD



Features

- Made from Polyamide 6,6, Halogen Free Cable Tie
- HEAVY DUTY Head/pawl integrally moulded for added strength, bent
- Smooth round edges, safe and will not cut insulation
- UV stabilised for outdoor use

Product Description

Our heavy-duty nylon cable ties are even stronger than our regular ties, making them perfect for applications that require a higher loop tensile strength.

CABAC nylon cable ties are made from halogen free PA66 nylon with an integrally moulded head and pawl. This, combined with intimate locking engagement between the pawl and strap teeth, means that our cable ties have high durability and strength without any metal parts.

CABAC heavy duty cable ties are designed to meet applicable strength requirements without sacrificing ease of use. In fact, our cable tie design incorporates several measures to improve comfort and safety. The product has smooth, round edges that are more comfortable to work with and reduce the risk of cuts to cable insulation or hands. The tail of the tie features a bent-tip with v-shaped grooving that prevents your grip from slipping. This means less effort during pick-

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

up, insertion and pull through.

Our black heavy-duty ties are UV stabilised for outdoor use.

Technical Data

Loop Tensile Strength: 54kg

Bundle Diameter: 102mm

Length: 370mm

Width: 7.6mm

Thickness: 2.1mm

Colour: Black

Conformant Standards: UL, Mil Spec, IEC, VDE, DIN.

Refer: Mil-S-23190E - testing

Smoke Emission: Low smoke/ halogen free

Material: PA66 with UV stabilisers

UV Stability: 2.5% carbon black for UV protection

Breakdown Voltage: 20 kV/mm

Moisture Content: 2.5% w.v. @ 23%/50%RH

Operating Temperature: -40 to 85 degrees Celsius

Flammability: Passed U.L. 94V-2

Tools & Accessories

Cable Tie Tensioning Tool

Part number: KTT3

Screw Mount

Part number: CTB9BK

Additional Information

Certificate of Materials Conformance

[Download Certificate of Materials Conformance](#)

IMH Resolution MEPC

[Download IMH Resolution MEPC](#)

ROHS

[Download ROHS](#)

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.