Product data sheet Characteristics

EVH4S11NC

EVlink Home, Charging station, 3P+N, attached cable 5m, 11kW, 16A, with RDC-DD





Main

Range	EVlink
Product name	EVlink Home
Product or component type	Charging station
Poles description	3P + N
Mounting mode	Wall-mounted
Offer type	Basic
Max power	11 kW 16 A 400 V
Number of charge point	1
Connection to the vehicle	Attached cable T2 bottom and top centre of enclosure 5 m
Quantity per set	Set of 1

Complementary

Rated supply voltage	400 V AC 50 Hz +/- 10 %	
Earthing system	TT	
	TN-S	
Number of inputs	1	
Input type	Auxiliary for dynamic energy management	
Control type	Red 1 emergency stop, function: 1 push-button	
Local signalling	Red, green and blue 1 LED, function: status indication	
Protection type	Earth-leakage protection	
Height	409 mm	
Width	282 mm	
Depth	148 mm	
Net weight	5.6 kg	
Colour	White (RAL 9003)	
Standards	EN 61851	
	IEC 61851-1	
	EN 61000-6-1	
	EN 61000-6-3	
Product certifications	CE	
	UKCA	
Maximum supply current	16 A	

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-3050 °C
Ambient air temperature for storage	-4085 °C
Relative humidity	595 %
Operating altitude	02000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	32.2 cm
Package 1 Width	40.0 cm
Package 1 Length	49.0 cm
Package 1 Weight	6.7 kg
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Height	79.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	66.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	[☑] China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Life Is On