



Main

| | |
|---------------------------|--------------------------|
| Product name | Easy56 |
| Product or component type | Switch and socket-outlet |
| Device short name | EY56C420 |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Control type | Rotary knob |
| Rotary handle padlocking | 2 padlocks 8 mm |
| Network type | AC |
| Outlet standard | Australian/New Zealand |

Complementary

| | |
|-------------------------------------|---|
| Mounting mode | Surface mounted |
| Plug, socket, control station shape | Straight |
| [In] rated current | 20 A |
| Pin number | 4 pins |
| Shape of pin | Tubular |
| [Ue] rated operational voltage | 500 V |
| Network frequency | 50 Hz |
| Protection type | Without protection |
| Material | Polycarbonate |
| Contacts material | Pins: brass |
| Connections - terminals | Screw terminals |
| Cable cross section | 1...16 mm ² |
| Cable entry number | 2 x M25 1 x M32 |
| Net weight | 0.82 kg |
| Height | 203 mm |
| Width | 101 mm |
| Depth | 101 mm |
| Colour | Body: grey (RAL 7035) Rotary handle: dark grey |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | AS/NZS 3133 AS/NZS 3123 |
| IP degree of protection | IP66 conforming to AS 60529 |
| Ambient air temperature for operation | -25...75 °C |
| Ambient air temperature for storage | -25...75 °C |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|