Product datasheet Characteristics

EY56P520

Easy56 Plug - 5 Pin - 20A - 500V



Product name	Easy56
Product or component type	Plug
Device short name	EY56P520
Plug, socket category	Low voltage
Poles description	3P + N + E
Pin number	5 pins
Shape of pin	Tubular
Outlet standard	Australian/New Zealand

Complementary

Main		
Product name	Easy56	
Product or component type	Plug	
Device short name	EY56P520	
Plug, socket category	Low voltage	
Poles description	3P + N + E	
Pin number	5 pins	
Shape of pin	Tubular	
Outlet standard	Australian/New Zealand	
Complementary		
Plug, socket, control station shape	Straight	
[In] rated current	20 A	
[Ue] rated operational voltage	500 V	
Network type	AC	
Network frequency	50 Hz	
Material	Polycarbonate: housing	
Contacts material	Pins: brass	
Connections - terminals	Screw terminals	
Cable cross section	14 mm²	
Cable outer diameter	716 mm	
Wire stripping length	1035 mm	
Cable entry	Cable gland	
Net weight	0.298 kg	
Height	78 mm	
Width	78 mm	
Depth	152 mm	
Colour	Plug: orange (RAL 2004) Body: clear	
Environment		
Standards	AS/NZS 3123	

Environment

Standards	AS/NZS 3123	

IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Ambient air temperature for storage	-2575 °C

Offer Sustainability

_	
EU RoHS Directive	Under investigation