





# FLEXI STREAMLINE 24V SINGLE COLOUR, CRI90 5M KIT FLBP24V5M - 6W/M

Versatile, CRI>90, COB LED single colour white, 5m strip kit, IP20, strip width 8mm.

### **Application**

Ideal for residential features

### **Design Specifications**

- 5 metre strip kit includes COB strip, with adhesive tape, plug and play driver
- Choice of 3000 / 4000 / 6000K, CRI>90
- Streamline COB LED chip technology, providing a smooth lighting profile
- Non-dimmable driver as standard
- Heat sink required for system performance, LED channel options refer this section
- Cuttable every 50mm NOTE: when cutting LED strips greater than 50% of the kit length, it is always important to calculate the remaining LED load to reconfirm its compatibility with the existing driver, as driver changes may be required with moderate reduction in loads

### **Performance**

• Dimmable - NO























## **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Watts per metre (W/m)	Beam Angle (°)	CRI	Luminous Flux Per Meter (lm/m)
	FLBP24V5M/WW	240	6	140	90	530
	FLBP24V5M/CW	240	6	140	90	580
	FLBP24V5M/DL	240	6	140	90	610

LEDs Per Metre	Cutting Interval	Colour Temp. (K)	Body Colour	Dim (mm)
320	50	3000	CLEAR	5000(L) x 8(W) x 2(H)
320	50	4000	CLEAR	5000(L) x 8(W) x 2(H)
320	50	6000	CLEAR	5000(L) x 8(W) x 2(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



What is the importance of EMC? Electromagnetic Compatibility, defines the use of different electronic devices (such as electrical appliances, medical equipment, IEDs and driversetc) to operate without interference with other devices. This is a mandatory label (and testing) requirement for Australian Lighting equipment covered by AS/NZS CISPR 15. ACMA also recognises equivalent standards CISPR 15 and EN 55015.

If you are unsure, ask your supplier for EMC compliance.