



## PIXIE FLEXI SMART KIT - FLP12V/SBT

PIXIE MASTER DEVICE - 2m or 5m smart lighting, warm white or neutral daylight strip kits

### Application

Home theatre, bar features, decorative task illumination demanding smart controls

### Design Specifications

- Smart LED strip kit, dimmable via PIXIE secondary device, or the PIXIE or PIXIE PLUS apps
- Dimming memory function
- High performance, stable, even light output
- Pre-wired for easy installation, plug-in & ready to use, cuttable every 50mm
- IP44 strip only, driver IP20
- NOTE: when cutting LED strips, it is always important to calculate the remaining LED load to reconfirm its compatibility with the existing driver, as driver changes may be required with moderate reduction in loads. Heat-sink required for system integrity and performance [LED channel options refer this section](#)



- 
- 
- 
- 
- 
- 
- 
- 

### Performance

- Dimmable - **YES**
- Dimmer Type - **PIXIE**

### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Beam Angle (°)	Body Colour	Dim (mm)	Watts per metre (W/m)
	FLP12V2M/WW/SBT	240	115	CLEAR	2000(L) x 8(W) x 2.5(H)	6
	FLP12V2M/NDL/SBT	240	115	CLEAR	2000(L) x 8(W) x 2.5(H)	6
	FLP12V5M/WW/SBT	240	115	CLEAR	5000(L) x 8(W) x 2.5(H)	6
	FLP12V5M/NDL/SBT	240	115	CLEAR	5000(L) x 8(W) x 2.5(H)	6

CCT (K)	LEDs Per Metre	CRI
3000	60	80
5000	60	80
3000	60	80
5000	60	80

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

