

Input	Lumens/Watt	Dimmable	CRI	Driver	Colour Temp.
230V	20,000lm	Available	>80	Integral	5000K

Warranty	Chip	Beam Angle	PFC	Material	IP
5yrs	182pcs 3030	>90deg	0.95	Aluminium	IP65

LED Highbay IP65

Introducing a New Generation of Highbay lighting. Gone is the inefficient Mercury Vapour, Metal Halide and even HPS metal reflector highbays.

Latest generation introduces massive system efficiency with up to 135 Lumens per Watt. The HUGO LED highbay features a highly efficient driver matched to 3030 SMD LEDs. Supplied complete with flex & plug top for quick installation

KEY FEATURES

- Current DC32-45V 3.4 Amps
- Complete with 1.5M flex & plug
- Working Temp -30°c to +50°c Humidity 10% to 95%
- Dimming options DALI 1-10V on request
- Suitable to operate with motion sensors
- Instant on off no cooling re strike time
- Constant Current Driver
- LED Life 50,000hrs (TM21 L70)
- Optical grade PC UV and Fire resistant lens
- Stainless Steel screws
- Excellent uniformity
- Compact Size
- Light Weight 3.2kg
- IES Files (Refer Website)
- Aluminium body
- Mounting hook
- SMH Ratio Nom 1.25:1



- CRI >80 (R9=4)
- Over Current Protection
- SAA Electrical approval

SKU CODE	WATT	LUMEN	LED Qty
HB150-5	150W	20,000lm	182pcs





hugolighting.com

DIMENSIONS

D:320mm, H: 150mm