POWER CLIP SET

HDT3916

Features
- Spring wire clip set with flexible insulated shank
- Approximate size 155 x 49mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 5A rating

4mm TEST PROBE SET

HDT3908

Features
- 4mm Tips that include banana style spring contacts
- Includes protective cap for PCB testing
- Approximate size 109 x 10mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 10A rating

CROCODILE CLIP SET

HDT3925

Features
- Wide opening grip claw with an insulated shank
- Approximate size 160 x 49mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 10A rating

2mm TEST PROBE SET

HDT3907

Features
- 2mm Hard tip points for electronic work
- Approximate size 102 x 10mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 10A rating

HOOK CLIP SET

HDT3926

Features
- Hook clamp with an insulated shank
- Approximate size 160 x 49mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 2A rating

SHARP TIP PROBE SET

HDT3923

Features
- Sharp 8mm point tip supplied with protective cap
- Approximate size 100 x 21mm
- Use with 4mm safety socket test leads HDT3081 and HDT3051
- CAT IV 600V / CAT III 1000V
- 6A rating

MODULAR TEST SET

HDT3051

Features
- The HDT3051 are DMM test leads and have safety shrouds with standard 4mm safety plugs
- Highly flexible PVC insulation 0.8mm² wire
- Straight connector on both ends of the leads, and recommended accessories for HDT3907, HDT3908, HDT3909, HDT3916, HDT3917, HDT3923, HDT3925 and HDT3926
- CAT IV 600V / CAT III 1000V
- 10A rating

MODULAR TEST SET

HDT3081

Features
- The HDT3081 are DMM test leads and have safety shrouds with standard 4mm safety plugs
- Highly flexible PVC insulation 0.8mm² wire
- Straight connector on one end and a right angled connector on the other end
- Recommended accessories for HDT3907, HDT3908, HDT3909, HDT3916, HDT3917, HDT3923, HDT3925 and HDT3926
- CAT IV 600V / CAT III 1000V
- 10A rating