

HYSWPC



Cleaning Guide:

Spraying cleaning products directly on to product is not recommended.

It is important to ensure that switches are turned off before cleaning.

Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic)

Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.

Do not wash the cover plates in water over 60°C.



Hyena Pull Cord Switch

- Pull Cord Switch 10AX 250V~ M80
- 2 Way + Loop 4 Terminal
- 4 terminal (Earth, Loop terminals) and (Live pins)
- Ø56mm
- Ø4.1mm terminal holes
- 10AX
- 1.8m Cord
- Mounting screw centres 36mm
- Easy mounting on timber or plaster surfaces
- Cord restraint mechanism that enables easy cable length adjustment



Catalogue Number	Description
HYSWPC	Pull Cord Switch 10AX 250V~

Certification Number: GMA-505281-EA

GSM Electrical (Australia) Pty Ltd

Level 2, 142-144 Fullarton Road, Rose Park SA 5067

P: 1300 301 838 F: 1300 301 778 E: service@gsm.com.au

www.gsm.com.au



Data Specification Sheet
Mar 2019