

PRODUCT SPECIFICATION CHART

| Product Name | Model Number | 200 mm Fan | 170 mm Fan | 8W R63 Standard LED Globe | 6W R63 LED Globe (Multi-option) | 10W R80 LED Globe (Multi-option) | 10W R80 Standard LED Globe | 10W R80 LED Globe (Motion Sensor) | Back Draught Flaps | Ducted to Outside | Capacity | | Half Heat Function | Cutout Dimensions (mm) | Max Ceiling Height | Max Height of Unit (mm) | Clearance Required above Unit (mm) | Minimum Ceiling Cavity Required (mm) | Watts (Fan in brackets) | Area Suitability with Shower (up to m ²) |
|-----------------------------|--------------|------------|------------|---------------------------|---------------------------------|----------------------------------|----------------------------|-----------------------------------|--------------------|-------------------|------------|--------------------|--------------------|------------------------|--------------------|-------------------------|------------------------------------|--------------------------------------|-------------------------|--|
| | | | | | | | | | | | Litres/Sec | m ³ /hr | | | | | | | | |
| Vivid 2 IN 1 (No Fan) | 11325 | NO FAN | | | | | | | | | N/A | N/A | | Template | 2.4m | 230 | 75 | 305 | 550 | N/A |
| Vivid 3 IN 1 | 11323 | | | | | | | | | | 86 | 310 | | Template | 2.4m | 230 | 75 | 305 | 590 (40) | 6.46 |
| Eco Vivid 3 IN 1 | 11344 | | | | | | | | | | 74 | 266 | | Template | 2.4m | 290 | 75 | 365 | 590 (40) | 5.54 |
| Triumph 2 IN 1 (No Fan) | 11317 | NO FAN | | | | | | | | | N/A | N/A | | Template | 2.4m | 230 | 75 | 305 | 550 | N/A |
| Triumph 3 IN 1 (275W) | 11311 | | | | | | | | | | 78 | 279 | | Template | 2.4m | 230 | 75 | 305 | 590 (40) | 5.81 |
| Triumph 3 IN 1 (375W) | 11312 | | | | | | | | | | 78 | 279 | | Template | 2.7m | 230 | 75 | 305 | 790 (40) | 5.81 |
| Eco Triumph 3 IN 1 | 11341 | | | | | | | | | | 72 | 257 | | Template | 2.4m | 290 | 75 | 365 | 590 (40) | 5.35 |
| Easy Duct Triumph | 11511 | | | | | | | | | | 58 | 210 | | Template | 2.4m | 215 (In-line fan) | 15 | 230 | 590 (40) | 4.38 |
| Prime 3 IN 1 | 12309 | | | | | | | | | | 86 | 310 | | 262 x 262 | 2.7m | 210 | 75 | 285 | 1140 (40) | 6.46 |
| Original 3 IN 1 | 11303 | | | | | | | | | | 79 | 283 | | 262 x 262 | 2.7m | 210 | 75 | 285 | 1140 (40) | 5.90 |
| Paramount 3 IN 1 | 12310 | | | | | | | | | | 107 | 385 | | 330 x 330 | 2.7m | 220 | 75 | 295 | 1140 (40) | 8.02 |
| Sensation 3 IN 1 | 12303 | | | | | | | | | | 109 | 392 | | 330 x 330 | 2.7m | 220 | 75 | 295 | 1140 (40) | 8.17 |
| Eco Sensation 3 IN 1 | 12343 | | | | | | | | | | 97 | 348 | | 330 x 330 | 2.7m | 220 | 90 | 310 | 1140 (40) | 7.25 |
| Easy Duct Sensation | 12511 | | | | | | | | | | 62 | 223 | | 330 x 330 | 2.7m | 215 (In-line fan) | 15 | 230 | 1140 (40) | 4.65 |
| Silhouette 3 IN 1 (375W) | 12301 | | | | | | | | | | 113 | 407 | | 330 x 330 | 3.3m | 220 | 75 | 295 | 1540 (40) | 8.48 |
| Vivid 3 IN 1 TRADE PACK | 11463 | | | | | | | | | | 86 | 310 | | Template | 2.4m | 230 | 75 | 305 | 590 (40) | 6.46 |
| Prime 3 IN 1 TRADE PACK | 11454 | | | | | | | | | | 86 | 310 | | 262 x 262 | 2.7m | 210 | 75 | 285 | 1140 (40) | 6.46 |
| Paramount 3 IN 1 TRADE PACK | 11475 | | | | | | | | | | 107 | 385 | | 330 x 330 | 2.7m | 220 | 75 | 295 | 1140 (40) | 8.02 |

★ Compatible

| Product Name | Model Number | LED Light Wattage | LED Colour Temp Cool White 4000K | Heat Lamp Wattage | Fan Size (mm) | Minimum Ceiling Height (m) | Maximum Ceiling Height (m) | Maximum Height of Unit (mm) | Capacity Litres/Sec | Capacity m ³ /hr | Clearance Required above Unit (mm) | Total Ceiling Cavity Required (mm) | Current Rating (Amps) | Watts (Fan in brackets) | Wall Switch Included | Ducting Included | Back Draft Flaps | Unit Dimensions (mm) | IPX4 Rated |
|----------------|--------------|-------------------|----------------------------------|-------------------|---------------|----------------------------|----------------------------|-----------------------------|---------------------|-----------------------------|------------------------------------|------------------------------------|-----------------------|-------------------------|----------------------|------------------|------------------|----------------------|------------|
| Ovation 3 in 1 | 31511 | 3 x 7W GU Frosted | | 800 | 180 | 2.2 | 2.7 | 230 | Up to 110 | Up to 396 | 15 | 245 | 3.6 | 850(50) | | | | 358W x476Lx166D | |

| Product Name | Model Number | LED Light Wattage | LED Colour Temp Warm White 3000K | LED Colour Temp Cool White 4000K | Heat Lamp Wattage | Fan Size (mm) | Minimum Ceiling Height (m) | Maximum Ceiling Height (m) | Maximum Height of Unit (mm) | Clearance Required above Unit (mm) | Capacity (litres/sec) | Capacity (m ³ /hr) | Total Ceiling Cavity Required (mm) | Current Rating (Amps) | Watts (Fan in brackets) | Wall Switch Included | Ducting Included | Back Draft Flaps | Unit Dimensions (mm) | IPX4 Rated |
|------------------------------|--------------|-------------------|----------------------------------|----------------------------------|-------------------|---------------|----------------------------|----------------------------|-----------------------------|------------------------------------|-----------------------|-------------------------------|------------------------------------|-----------------------|-------------------------|----------------------|------------------|------------------|----------------------|------------|
| Luminate Single White | 31411 | 25 | | | 800 | 170 | 2.2 | 2.7 | 230 | 15 | 133 | 480 | 245 | 3.6 | 875(75) | | | | 367Wx483Lx198D | |
| Luminate Single Silver | 31412 | 25 | | | 800 | 170 | 2.2 | 2.7 | 230 | 15 | 133 | 480 | 245 | 3.6 | 875(75) | | | | 367Wx483Lx198D | |
| Luminate Dual White | 32411 | 25 | | | 1600 | 170 | 2.2 | 3.3 | 230 | 15 | 133 | 480 | 245 | 7.0 | 1675(75) | | | | 367Wx733Lx198D | |
| Luminate Dual Silver | 32412 | 25 | | | 1600 | 170 | 2.2 | 3.3 | 230 | 15 | 133 | 480 | 245 | 7.0 | 1675(75) | | | | 367Wx733Lx198D | |
| Luminate Vent White | 35401 | N/A | | | N/A | 170 | N/A | N/A | 230 | 15 | 111 | 400 | 245 | 0.3 | 0(75) | | | | 367Wx243Lx210D | |
| Luminate Vent Silver | 35402 | N/A | | | N/A | 170 | N/A | N/A | 230 | 15 | 111 | 400 | 245 | 0.3 | 0(75) | | | | 367Wx243Lx210D | |
| Luminate Vent & Light White | 34401 | 17 | | | N/A | 170 | N/A | N/A | 230 | 15 | 111 | 400 | 245 | 0.4 | 90(75) | | | | 367Wx243Lx210D | |
| Luminate Vent & Light Silver | 34402 | 17 | | | N/A | 170 | N/A | N/A | 230 | 15 | 111 | 400 | 245 | 0.4 | 90(75) | | | | 367Wx243Lx210D | |
| Luminate Heat White | 36411 | N/A | | | 800 | N/A | 2.2 | 2.7 | 160 | 75 | N/A | N/A | 235 | 3 | 800(0) | | | | 367Wx326Lx160D | |
| Luminate Heat Silver | 36412 | N/A | | | 800 | N/A | 2.2 | 2.7 | 160 | 75 | N/A | N/A | 235 | 3 | 800(0) | | | | 367Wx326Lx160D | |
| Neo Single White | 31111 | 3x7W-GU10 | | | 800 | 170 | 2.2 | 2.7 | 230 | 15 | 96 | 346 | 245 | 3.6 | 875(75) | | | | 361Wx481Lx170H | |
| Neo Single Silver | 31112 | 3x7W-GU10 | | | 800 | 170 | 2.2 | 2.7 | 230 | 15 | 96 | 346 | 245 | 3.6 | 875(75) | | | | 361Wx481Lx170H | |
| Neo Dual White | 32111 | 3x7W-GU10 | | | 1600 | 170 | 2.2 | 3.3 | 230 | 15 | 96 | 346 | 245 | 7.0 | 1675(75) | | | | 361Wx735Lx170H | |
| Neo Dual Silver | 32112 | 3x7W-GU10 | | | 1600 | 170 | 2.2 | 3.3 | 230 | 15 | 96 | 346 | 245 | 7.0 | 1675(75) | | | | 361Wx735Lx170H | |
| Neo Vent White | 35101 | N/A | | | N/A | 170 | N/A | N/A | 230 | 15 | 104 | 375 | 245 | 0.3 | 0(75) | | | | 361Wx237Lx200H | |
| Neo Vent Silver | 35102 | N/A | | | N/A | 170 | N/A | N/A | 230 | 15 | 104 | 375 | 245 | 0.3 | 0(75) | | | | 361Wx237Lx200H | |
| Neo Vent n Lite White | 34101 | 3x7W-GU10 | | | N/A | 170 | N/A | N/A | 230 | 15 | 104 | 375 | 245 | 0.4 | 96(75) | | | | 361Wx237Lx200H | |
| Neo Vent n Lite Silver | 34102 | 3x7W-GU10 | | | N/A | 170 | N/A | N/A | 230 | 15 | 104 | 375 | 245 | 0.4 | 96(75) | | | | 361Wx237Lx200H | |
| Neo Heat White | 36111 | N/A | | | 800 | N/A | 2.2 | 2.7 | 160 | 75 | N/A | N/A | 235 | 3.3 | 800(0) | | | | 361Wx320Lx156H | |
| Neo Heat Silver | 36112 | N/A | | | 800 | N/A | 2.2 | 2.7 | 160 | 75 | N/A | N/A | 235 | 3.3 | 800(0) | | | | 361Wx320Lx156H | |

| Product Name | Model Number | 170 mm Fan | 200 mm Fan | 250 mm Fan | Light & Exhaust Fan | Back Draught Flaps | Ducted to Outside | Capacity (litres/sec) | Capacity (m ³ /hr) | Area Suitability Room With Shower (m ²) | Light | Cutout Size (mm) | Clearance Required Above Unit (mm) | Watts | IP Rating |
|----------------------------------|--------------|------------|------------|------------|---------------------|--------------------|-------------------|-----------------------|-------------------------------|---|--------------------------------|------------------|------------------------------------|-------|-----------|
| Ventflo 200mm | 10330 | | | | | | | 86 | 310 | 6.46 | N/A | 240 | 180 | 35 | |
| Ventflo 250mm | 10331 | | | | | | | 149 | 538 | 11.21 | N/A | 290 | 180 | 35 | |
| Eco Ventflo 200mm | 10332 | | | | | | | 129 | 465 | 9.68 | N/A | 242 | 215 | 35 | IPX2 |
| Eco Ventflo 250mm | 10333 | | | | | | | 173 | 624 | 13 | N/A | 295 | 260 | 45 | IPX2 |
| Ducted Ventflo Fan 200mm | 10334 | | | | | | | 77 | 280 | 5.83 | N/A | 240 | 210 | 45 | IP24 |
| Ducted Ventflo Fan & Light 200mm | 10336 | | | | | | | 77 | 280 | 5.83 | 12W LED Panel 4000K Cool White | 240 | 210 | 45 | IP24 |
| Ducted Ventflo Fan 250mm | 10337 | | | | | | | 100 | 360 | 7.50 | N/A | 295 | 242 | 60 | IP24 |
| Ducted Ventflo Fan & Light 250mm | 10338 | | | | | | | 100 | 360 | 7.50 | 12W LED Panel 4000K Cool White | 295 | 242 | 60 | IP24 |
| Ventflo Vent N Lite Deluxe | 10363 | | | | | | | 92 | 321 | 6.68 | 2 X 42W Halogen (incl) | 262 x 262 | 285 | 124 | |
| Ventflo Easy Duct Extraction | 10380 | | | | | | | 55 | 198 | | N/A | 160 dia. | 230 | 40 | |