



All dimensions are in millimeters.

Technical Specifications

Maximum	30A
Rated Voltage(Un)	AC 230V
Rated frequency	50(60)Hz
Phase	Single Phase
Starting Current	0.4%Ib
Insulation Performance	AC voltage withstand 2kV for 1 minute; Impulse voltage withstand 6kV -- 1.2/50μs waveform
Accuracy Class	Class 1.0
Dimensions	65mm(L) 116mm(H) 17.5mm(W)
Installation method	DIN rail
Humidity	Less than 75%
Operating temperature	-25°C ~ +55°C
Storage temperature	-30°C ~ +65°C

Code: KWHM/1

Split Qty: 1

Carton Qty: 100

www.pulset.com



7 857381 003150

PULSET Pty Ltd ABN. 33 095 649 228 All Correspondence: P.O Box 6644, Wetherill Park BC NSW 2164

1300 Pulset (785738) P. +61 2 9756 5000

E. mail@pulset.com W. www.pulset.com

SYDNEY

02 9756 5000

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Pulset nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.