



DIMMABLE CONVERSION KIT LCT30TC/D - 20W

Dimmable 20 watt LED conversion kit, with selectable colour temperature

Application

Energy efficient LED lamp solutions, ideal for apartments and residential spaces

Design Specifications

- Aluminium heat sink mounted base, Electrical class I
- Opal polycarbonate lens
- High efficiency SMD LED chips, integral selectable CCT 3000K/4000K/5700K
- Requires installation into suitable fitting, dimensions 300mm x 22mm
- Integral trailing edge dimmable 20 watt LED driver
- Supplied with mounting clips and screws for easy installation



Performance

Dimmable - **YES**

Dimmer Type - **Trailing edge**

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Dimmable
LCT30TC/D	240	20	1800/2000/1900	3000/4000/5700	80	YES


Model No.	Diameter (mm)
LCT30TC/D	300

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

Dimensions



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
UNIFIT SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

