

CARBON MONOXIDE ALARM





MODEL: Mini-968/10Y

Key Information

Product or component	Carbon Monoxide Detector
Device application	Early detection of Carbon Monoxide Leakage
Sensor type	Electrochemical Sensor
Colour	White
Quantity	1
Packaging type	Carton

Power Supply	DC Sealed Battery
Battery Type	3V Lithium Battery
Battery Life	10 YR
Operating Current	≤150mA at 3V
Standby Power	≤10mA
Detection Type	Carbon Monoxide
Function	Hush Function CO Detection Local Alarm
Control Type	Button for Test/ Hush Function
Response Time	50 PPM [60–90 MIN] 100 PPM [10–40 MIN] 300 PPM [<3 MIN]
Noise Level	85 dB at 3M Minimum
Time Delay Range	10 MIN: for Hush 10 HR: for Silence
Local Signal	Sound: Alarm Sound: Signal Power Activation Signal (Green Light) Fault Warning (Yellow Light Flash 2 times) End of Life Signal (Yellow Light Flash 3 times) CO Gas Warning Signal (Red Light)
Type of Installation	Indoor
Device Mounting	Surface
Mounting Support	Wall-mount
Fixing Mode	By Screws
Dimension	90 x 22 x 90 MM [L x W x H]
Ambient Air Temperature for Operation	-10...40°C
Relative Humidity	10...90%
Product Certifications	TUV
Standards	EN50291-1:2010+A1:2012



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Red Smoke Alarms PTY. LTD nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.