

## Product data sheet

### Characteristics

# ML2031RCD10-WE

## CLIPSAL RCD - 2P - 10mA - 20A - 250V



### Main

|                           |                         |
|---------------------------|-------------------------|
| Product or component type | Residual current device |
| Product brand             | Clipsal                 |
| Poles description         | 2P                      |
| [In] rated current        | 20 A                    |
| Earth-leakage sensitivity | 10 mA                   |

### Complementary

|                                |                                     |
|--------------------------------|-------------------------------------|
| [Ue] rated operational voltage | 250 V AC                            |
| Size                           | 116 x 76 mm conforming to DIN 43880 |
| Colour                         | White electric                      |

### Environment




|           |             |
|-----------|-------------|
| Standards | AS/NZS 3190 |
|-----------|-------------|

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 176.0 g  |
| Package 1 Height             | 7 cm     |
| Package 1 Width              | 9.1 cm   |
| Package 1 Length             | 11.7 cm  |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 5        |
| Package 2 Weight             | 0.996 kg |
| Package 2 Height             | 12 cm    |
| Package 2 Width              | 9.1 cm   |
| Package 2 Length             | 36 cm    |
| Unit Type of Package 3       | CAR      |
| Number of Units in Package 3 | 50       |
| Package 3 Weight             | 9.96 kg  |
| Package 3 Height             | 36 cm    |
| Package 3 Width              | 34.5 cm  |
| Package 3 Length             | 40.5 cm  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |