

MAJOR

LOCK

TINUOUS

OFF

1251

250

MT560

IEC 61010-1

CAT IV

600V

500V

1000V

400Ω

IEC

61010-1

000

CAT III

10000

750V

CAT III

LOCK

HOLD

MT560 Insulation Tester

The MT560 has a large dual display with a bargraph indicating the insulation resistance. This compact handheld meter has four test ranges: 125V, 250V, 500V and 1000V source for the test and under each range it can supply more than 1mA current to feed the capacitance load. The tester features AC and DC voltage ranges as well as a battery indication. Should AC voltage be present, the LCD display will indicate to the operator the AC voltage value, regardless of what range the meter is on except in the Off position. Other features include a data hold function, a bright white LED back light and a continuity buzzer.



- Four test ranges 125V-250V-500V-1000V
- MIN/MAX Record mode
- Measures AC Voltage to 750V and DV Voltage to 1000V
- Large Dual LCD display with bargraph
- Live Circuit detection prevents insulation tests if voltage >30V
- Auto Null of test lead resistance
- 1mA output current on insulation test
- 200mA short circuit on continuity range
- Continuity Buzzer
- Automatic discharge of capacitive voltage after test for added protection
- Data Hold function
- Lock down Test Button for continuous use
- Hands free strap and magnet supplied as standard accessories
- Rubber overmould housing
- Illuminated display

Function	Range	Accuracy
Insulation resistance	125V - 4MΩ	±(2.0% +10)
Insulation resistance	250V - 40MΩ	±(2.0% +10)
Insulation resistance	500V - 400MΩ	±(2.0% +10)
Insulation resistance	1000V - 4000MΩ	±(3.0% +10)
Short circuit current	1.0mA	
Measuring Current	200mA@4.5V	
DC voltage	0 - 1000V	±(0.8% +3)
AC voltage	0 - 750V	±(1.2% +10)
Resistance	40Ω - 400Ω	±(1.2%+3)
Size	200 x 92 x 50mm	
Weight	700g	



and LED Backlight



ACV & DCV



Four insulation test ranges



MT560

ZERO

Digital Insulation Tester

Contact Us South Africa

Australia

🌐 www.major-tech.com 🛛 🖂 sales@major-tech.com

🌐 www.major-tech.com.au 🛛 info@major-tech.com.au