

Product data sheet

Characteristics

MX9C212510

Contacteur, MAX9, 1 NO, 25A, Ue=240VAC, Uc=24VAC, 1 module



Main

| | |
|--------------------------------|-----------------|
| Range | MAX9 |
| Product or component type | Contacteur |
| Device application | Control circuit |
| Poles description | 1P |
| [Ie] rated operational current | 25 A AC-7A |
| Pole contact composition | 1 NO |
| Network type | AC |
| Utilisation category | AC-7A |
| Control type | Remote control |
| [Uc] control circuit voltage | 24 V AC 50 Hz |

Complementary

| | |
|--|--|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 240 V AC 50 Hz |
| Maximum power | 1.3 W at 240 V AC 50 Hz |
| [Ui] rated insulation voltage | 500 V AC 50 Hz conforming to EN 61095 |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Switching frequency | 100 switching operations/day |
| Hold-in power consumption in VA | 3.8 VA |
| Inrush power in VA | 15 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |
| Comb busbar and distribution block compatibility | NO |
| 9 mm pitches | 2 |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 63 mm |
| Net weight | 120 g |
| Colour | White (RAL 9003) |
| Mechanical durability | 1000000 cycles |
| Electrical durability | 100000 cycles 24 V 25 A AC 50 Hz |
| Connections - terminals | Power: tunnel type terminal1 cable(s) 1.5...4 mm ² flexible Power: tunnel type terminal2 cable(s) 1.5...2.5 mm ² flexible Power: tunnel type terminal1 cable(s) 1.5...6 mm ² rigid Power: tunnel type terminal2 cable(s) 1.5...2.5 mm ² rigid Control: tunnel type terminal1 cable(s) 0.5...4 mm ² flexible Control: tunnel type terminal2 cable(s) 0...2.5 mm ² flexible Control: tunnel type terminal1 cable(s) 0.5...6 mm ² rigid Control: tunnel type terminal2 cable(s) 0...2.5 mm ² rigid |
| Tightening torque | 0.8 N.m |
| Wire stripping length | 10 mm |
| Product compatibility | No auxiliary |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|----------------------------|--|
| Market segment | Residential |
| Temperature derating table | 40 °C (25 A) 50 °C (23.8 A) 60 °C (20 A) |

Environment

| | |
|---------------------------------------|--|
| Quality labels | RCM |
| Noise level | 30 dB |
| Heat dissipation | 1.4 W at 50 Hz |
| IP degree of protection | IP20 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 2 |
| Overvoltage category | III |
| Tropicalisation | Severity B |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...70 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 124 g |
| Package 1 Height | 8 cm |
| Package 1 width | 2.3 cm |
| Package 1 Length | 10 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 88 |
| Package 2 Weight | 11.412 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |