

## FEATURES & BENEFITS

- UV resistant
- Vibration resistant - Ratchet action
- Complete with TPE rubber gasket
- 1.5 metric threads
- CE and RoHS compliant
- Low smoke - Halogen free

## SPECIFICATIONS

Materials: Gland - Nylon PA66  
Gasket - TPE

Weatherproof rating: IP68

Operating temperature: -40°C to 100°C

Flammability: UL94V-2



## DIMENSIONS

Code	A (mm)	B (mm)	C (mm)	D (mm)	Cable Size (mm)
NCG-M12/B	5	17	8	15.5	3 - 6
NCG-M16/B	5	22	15	21.5	4 - 9
NCG-M20/B	5.5	26.5	15	26.5	6 - 12
NCG-M25/B	6.5	32.5	15	32.5	8 - 16
NCG-M32/B	7	38.5	15	41.5	14 - 22
NCG-M40/B	7.5	55.5	20	53.5	22 - 33
NCG-M50/B	10.5	66	18.5	56	27 - 37
NCG-M63/B	11.5	80	20	68	32 - 47



## CABLE GLANDS - NYLON RANGE

Code	Description	Packing	MOQ	Ctn
NCG-M12/B	Nylon Cable Gland - 12mm - Black	100	100	4500
NCG-M16/B	Nylon Cable Gland - 16mm - Black	50	50	1350
NCG-M20/B	Nylon Cable Gland - 20mm - Black	40	40	1440
NCG-M25/B	Nylon Cable Gland - 25mm - Black	20	20	600
NCG-M32/B	Nylon Cable Gland - 32mm - Black	15	15	480
NCG-M40/B	Nylon Cable Gland - 40mm - Black	6	6	300
NCG-M50/B	Nylon Cable Gland - 50mm - Black	3	3	192
NCG-M63/B	Nylon Cable Gland - 63mm - Black	2	2	96