



## Main

|                           |            |
|---------------------------|------------|
| Range                     | Pro Series |
| Product or component type | Switch     |
| Device application        | Lighting   |
| Colour tint               | White      |
| Type of packing           | Polybag    |
| Quantity per set          | Set of 10  |

## Complementary

|                                |  |
|--------------------------------|--|
| Device presentation            | Complete product   |
| Control type                   | Rocker   |
| Device mounting                | Wall   |
| Installation direction         | Vertical   |
| Switch function                | 1-pole 1/2-way   |
| Number of rocker               | 2  |
| Rated current                  | 20 A/16 AX   |
| [Ue] rated operational voltage | 250 V  |
| Material                       | PC (polycarbonate)<br>PP (polypropylene)<br>ABS (acrylonitrile butadiene-styrene)<br>POM (polyoxymethylene)  |
| Fixing mode                    | By screws  |
| Surface finish                 | Glossy   |
| Surface treatment              | Untreated  |
| Connections - terminals        | Screw terminal   |
| Clamping connection capacity   | 1 x 1.5...4 x 1.5 mm <sup>2</sup> for rigid or stranded cable(s)<br>3 x 2.5 mm <sup>2</sup> for stranded cable(s)<br>1 x 4 mm <sup>2</sup> for stranded cable(s) |
| Height                         | 113 mm   |
| Width                          | 38 mm  |
| Depth                          | 40 mm  |
| Net weight                     | 0.063 kg   |

## Environment

|                                       |           |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity                     | 10...95 % |
| Product certifications                | RCM       |