

Datasheet

Weatherproof Light Sensitive Switch IP56, 10A

CAT. NO. PE170/10



A brand of legrand



Cat. No.	PE170/10
Description	Weatherproof Light Sensitive Switch
Operation	Turn Lights on from sunset to sunrise
Contacts	Normally Open
Colour	Grey base with opalescent cover
Supply voltage	230 - 240 Va.c. \pm 6%
Frequency	50 Hz
Connection Type	3 wires
Maximum Load	2400W Incandescent 2400W Halogen 1000VA Compact Fluorescent 1000W LED 500VA High intensity discharge 1500VA Fluorescent tube
Minimum Load	5W
Stand-by power consumption at V_{in}	\leq 1 W
Operating Temperature	0° to 50°C

Weatherproof Light Sensitive Switch IP56, 10A

CAT. NO. PE170/10



A brand of **legrand**



FEATURES

- Suitable for all commercial and residential installations.
- Weatherproof rating IP56.
- Multiple side and back cable entries: Ø 25mm.
- Low standby power consumption < 1W
- Surface mount.
- Easy to install.

Single product		
Cat. No.	Dimensions	Barcode
PE170/10	88 W x 72 H x 115 Dmm	9310539013848

Outer box (QTY 60)		
Cat. No.	Dimensions	Barcode
PE170/10	397 W x 375 H x 390 Dmm	9321001434580

Legrand - Australia
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.hpm.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.