

TECHNICAL DATA SHEET

## **Stanilite®**

# Platinum exit LED Quickfit®



### Range


Platinum range

## **Product group**

Exit LED Quickfit



#### **Features**






- Low power consumption and LED light source for reduced operation and maintenance costs
- Advanced charging technology combined with Lithium iron phosphate battery for long life and low maintenance



- Quickfit unique steel slide connect bracket for quick installation and easy maintenance
- Includes all pictograph diffuser options for single or double sided installation
- Universal wall/ceiling mounting, can also be rod or wire suspended
- Retrofit capability; fits into any existing Quickfit mounting bracket
- Frame only available for upgrade of installed product (less mounting bracket and diffusers) will accept existing diffusers

Catalogue no.	Description	
EM products		
PQFLEDP	Platinum exit LED Quickfit pictograph	
Accessories		
MQFCL	Cantilever bracket	
QFWGCM	Wire guard - ceiling	
QFWGWM	Wire guard - wall	
PWQFKITPOLY	IP65 kit - polycarbonate for single or double sided installation	
PWQFKITACRY	IP65 kit - acrylic for single or double sided installation	
29-PIQFVERT	Quickfit pictograph vertical insert pack 4 piece set *	
	Note: * Refer to the installation manual for vertical installation requirements	
Spare parts		
03-01302P	Battery LiFePO4 3.2V 3.2Ah	
31-PQFCC	Diffuser Quickfit LED includes single sided pictograph decal	
PQFLEDP-LB	Platinum exit LED Quickfit less bracket pictograph	
PQFLEDP-FR	Platinum exit LED Quickfit frame only	



Dimensions				
	Length	Width	Height (incl. bracket)	
	379mm	72mm	214mm	
Weight				
	Model	Weight		
	EM	1.8kg		
Construction				
	Part	Construct	Construction	
	Body	UV/FR ABS	UV/FR ABS body	
	Diffuser	Opal acryli	Opal acrylic	
	Bracket	White pow steel	White powder coated zinc steel	

Light source			
	Model	Light source	
	EM	Multiple LED 1.6W	
Power consumption			
	Model	Power consumption	·
	EM	3.2W	
			Note: Preliminary result
Photometrics		,	·
	Model	Class	Classification
	EM	Co	D3.2
		<b>C</b> 90	D3.2
			Note: Preliminary result

## Note:

<sup>–</sup> Designed to comply with AS2293 and meet relevant Australian EMC standards