

Product data sheet

Characteristics

RMSW180

Switch disconnecter, Resi MAX, 1P, 80A



Main

| | |
|---------------|----------|
| Range | Resi MAX |
| Product brand | Clipsal |

Complementary

| | |
|---|---------------------|
| Product or component type | Switch disconnecter |
| [Ue] rated operational voltage | ≤ 250 V AC |
| [In] rated current | 80 A |
| Rated conditional short-circuit current | 10 kA |
| Number of poles | 1 |
| Mounting support | DIN rail |

Environment

| | |
|-------------------------|------------------|
| IP degree of protection | Front face: IP20 |
|-------------------------|------------------|

Packing Units

| | |
|------------------|-----------|
| Package 1 Weight | 240.000 g |
| Package 1 Height | 7.500 cm |
| Package 1 width | 5.400 cm |
| Package 1 Length | 8.500 cm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.