RWBB

Mounting Base for Main Powered Smoke Alarm - Wireless Interconnect
For use with R240 & R240RC

Key Information

Product brand	Red Smoke Alarms
Product or component	Mounting Base
Device application	Mounting
Colour	Black (RAL 9005)
Quantity per set	Set of 1
Type of packing	Carton

Complementary

[US] rated supply voltage	220...240 V AC
[le] rated operational current	40mA maximum
Battery Type	Sealed rechargeabe
Battery life	10 Year
Transmission Frequency	433.92 MHz
Number of device	Interconnect 40pcs smoke alarm (wired or wireless interconnected)
Operating Distance	30m indoor use line of sight 100m in free field
Remote control type	Only with wireless remote control switch with max 30m
Time delay range	2 min for pairing
Connections - Terminals	For live: Screw terminal with 2 x 15mm2 wiring capacity
	For neutral: Screw terminal with 2 x 1.5 mm^2 wiring capacity
	For earth loop: Screw terminal with 2 x 15mm^2 wiring capacity
	For interconnect: Screw terminal with 2 x 15mm^2 wiring capacity
Local Signally	1 red LED flashing once every 10s for low battery
Type of installation	Indoor
Diameter	140 mm
Height	55 mm

Environment

Ambient air temperature for operation	0...45°C
Relative humidity	5...95%
Standards	AS 4268

red SMOKE ALARMS

Data Sheet

RWBB