Product datasheet

Specifications



Switched Socket, Iconic, 2 switch & 2 socket, horizontal, 10A, 230/240V, silver

S3025-SV

Main

Range of product	Iconic
Range	Iconic
Product or component type	Switched socket
Device presentation	Complete product
Product brand	Clipsal
Outlet poles configuration	2P + E with shutter
Outlet standard	Australian
Colour tint	Silver (SV)
Main colour tint	Silver
Switch application	On/off switching

Complementary

Socket-outlet type	Twin switched socket-outlet
Device mounting	Flush
Mounting position	Horizontal
Number of rocker	2
fixing mode	By screws
Installation direction	Horizontal
Surface finish	Glossy
surface treatment	Anodised
Rated current	10 A at 250 V AC 50 Hz
Connections - terminals	screw terminals
Clamping connection capacity	1 x 2.5...4 x 2.5 mm² for rigid cable(s) 1 x 2.5...4 x 2.5 mm² for stranded cable(s) 1 x 2.5...4 x 2.5 mm² for flexible cable(s)
Wire stripping length	16 mm
Material	Metal
Height	82 mm
Width	126 mm
Depth	36.5 mm
Embedding depth	28 mm
Network frequency	50 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ue] rated operational voltage	250 V
Rated current	10 A
Network type	AC
Connections - terminals	Screw terminals
Socket number	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.3 cm
Package 1 Width	15 cm
Package 1 Length	10.2 cm
Package 1 Weight	173 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	23 cm
Package 2 Width	26.7 cm
Package 2 Length	34.1 cm
Package 2 Weight	3.76 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**11 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**1 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**9 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.3 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
Halogen-free status	**Halogen free product**
PVC free	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**43**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative













