



## KINGSTON DIMMABLE SL2115/TCD - 13W/30W

Dimmable, super low profile LED Oyster 13, 24 or 30 watt, with selectable CCT, IP54

### Application

A perfect choice for apartments, residential or commercial spaces

### Design Specifications

- Selectable CCT 3000K / 4000K / 5700K
- High performance IP54 opal PC mounting base and LED optical module
- High efficiency LED optics, CRI > 80, 100° beam distribution
- Integral, dimmable LED driver, choice of 13, 24 or 30 watt
- Double insulated, ceiling mount



### Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**



### Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Dimmable
SL2115/25TCD	240	13	1000/1150/1050	3000/4000/5700	80	YES
SL2115/30TCD	240	24	1900/2100/2000	3000/4000/5700	80	YES
SL2115/40TCD	240	30	2600/2800/2700	3000/4000/5700	80	YES

Model No.	Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)
SL2115/25TCD	100	White	244	26(H)	0.5
SL2115/30TCD	100	White	294	26(H)	0.66
SL2115/40TCD	100	White	420	30(H)	1.14

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".