



UNITREK SRC9017TC - 9W

Unitrek, architectural cylindrical recessed mount profile, with selectable CCT and dual power

Application


Designed for decorative retail or residential applications

Design Specifications

- Polyamide cylindrical body profile
- High efficiency LED, with selectable CCT
- Multi-faceted reflector system, standard beam distribution 40 degree
- Polycarbonate optical lens
- Integral constant current trailing edge dimmable LED driver, with selectable power

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)
	SRC9017TC/BK	240	10/15	1000/1150/1100	3000/4000/5700	40
	SRC9017TC/WH	240	10/15	1000/1150/1100	3000/4000/5700	40

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	BLACK	72	90	195(L)
YES	80	WHITE	72	90	195(L)

Note: Lumen (lm) displayed are at FULL power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECO GEM SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

