



Flat TPS Cables 450/750V V-90 PVC insulated, NON-Migratory 5V-90 PVC sheathed.

Application: For light to medium industrial use. For festoon systems and other applications. Suitable for all building internal wiring applications. Insulation & sheathing material is non migratory and suitable for use in cable that are in contact with polystyrene ,ABS,polycarbonate and acrylic.

Conductor: Plain annealed copper (AS/NZS 1125)

Insulation: V-90 PVC

Sheath: NON-Migratory 5V-90 PVC

Standard: AS/NZS 5000.2

Packing Length: 100m, 500m

Normal Operating Temperature: -20°C to 90°C



Typical Features:

Electra Cables Part No.	Stranding No./mm	Conductor area mm	Insulation Thickness mm	Sheath Thickness mm	Nom. O/D mm	Approx. Mass kg/100 m
SRF3015VHT	7/0.50	1.5	0.6	0.9	10.0×4.6	8.5
SRF3025VHT	7/0.67	2.5	0.7	1.0	12.4×5.5	13.5
SRF4015VHT	7/0.50	1.5	0.6	0.9	12.6×4.6	11.0
SRF4025VHT	7/0.67	2.5	0.7	1.0	15.8×5.5	17.5

These cables are suitable for installations:

- . . wall or roofing insulation material
- . .caravans
- . .cold rooms
- . .transportable buildings



Note: Other types or other lengths of the above cables can be manufactured according to customers' specifications.