SYN 160 a

Item no.: 1600001



Time and light control Analogue time switches

Description

- Analogue time switch
- 1 channel
- Daily program
- Without power reserve
- 96 switching segments
- Synchronised with mains
- Shortest switching time: 15 minutes
- Screw terminals
- Manual switch with 3 positions: Permanent ON/AUTO/continuous OFF



Technical data

	SYN 160 a
Operating voltage	230 V AC
Frequency	50 Hz
Number of channels	1
Width	1 modules
Installation type	DIN rail
Type of connection	Screw terminals
Drive	Synchronous motor
Program	Daily program
Switching capacity at 250 V AC, cos φ = 1	16 A

	SYN 160 a
Switching capacity at 250 V AC, $\cos \varphi = 0.6$	4 A
Incandescent/halogen lamp load	1000 W
Energy saving lamps	150 W
LED lamp < 2 W	30 W
LED lamp 2-8 W	300 W
LED lamp > 8 W	300 W
Shortest switching times	15 min
Programmable every	15 min
Time accuracy at 25 °C	Synchronised with mains
Type of contact	NO contact

SYN 160 a

Item no.: 1600001




Technical data

SYN 160 a
Potential-free and phase- independent
96
~0.9 W
0.7 W
VDE

	SYN 160 a
Housing and insulation material	High-temperature resistant, self- extinguishing thermoplastic
Type of protection	IP 20
Protection class	II according to EN 60 730-1
Ambient temperature	-25°C 50°C

Connection example





SYN 160 a

Item no.: 1600001



Scale drawings





Accessories

Wall mounting kit 17,5 mm

Item no.: 9070065



Front panel kit Item no.: 9070001

