

## PHASE COLOURED LEAD SET



### Part No. AL30RWBKIT

Set of double insulated silicone insulated test leads with right angled banana plugs and shrouded 4mm banana plug probes in colours red, white and blue.

CAT III  
1000V

EA QTY 1

|                              |   |
|------------------------------|---|
| <b>Compliance and Safety</b> | CAT III 1000V, CAT II 1000V without cap<br>Crocodile clips CATIV1000V |
| <b>Length</b>                | 1000mm  |
| <b>Kit Includes</b>          | Three large crocodile clips   |

## SPARE LEAD TO SUIT BM877



### Part No. AL-BM877IN

AL-BM877IN is an accessory for BM877 ONLY. The AL-BM877IN is a spare lead for remote insulation testing DMM BM877.

EA QTY 1

## FUSED LEAD SET CATIV WITH 10A FUSES



### Part No. AL-57F10A

The AL57F10A is a set of red and black high quality silicon fused pluggable probes and 1.5m test leads.

- CATIII 1000V and CATIV 600V with protective cover
- Fuses 100V, 11A, 20kA AC or DC
- 2mm probe tips under protective cover
- DMM with 10MΩ voltage impedance measurement with 1000Ω resistor bypass if fuse is blown
- Leads 4mm shrouded straight and 90° angled banana plugs connectors for connection to probes and standard meter connections

CAT IV  
600V  
10A

EA QTY 1

|                              |   |
|------------------------------|---|
| <b>Compliance and Safety</b> | IEC61010-0312002+A12008. CATIII 1000V & CATIV 600V with protective cover. CATII 1000V without the protective cover. |
| <b>Contents</b>              | Red and black test leads, red and black probes with 10A fuses   |
| <b>Dimensions</b>            | 1.5m long leads   |
| <b>Weight</b>                | 201g for leads, fuses and probes  |

## SPLITTER ACTIVE 10A PLUG/ LEADS



### Part No. TEL-AUS10A

Australian 10A plug to universal socket for easy access to measuring the load of an appliance. There are two measuring positions for x1 and x10 and access for voltage checks with 2mm probes.

- Designed for the Australian and New Zealand market
- Use with any clamp meter
- x10 mode allows for more accurate measurement of low current devices
- x1 mode allows for direct current reading
- 4mm voltmeter input jacks
- 10 amp capacity
- 19cm plug cord for greater flexibility

CAT III  
600V

EA QTY 1

|  |                        |
|--|------------------------|
| <b>Input plug</b>                                    | Australia/NZ           |
| <b>Output Socket</b>                                 | Australia/NZ           |
| <b>Cord Length</b>                                   | 19cm± 1cm              |
| <b>Max. Voltage</b>                                  | 250Vac (±10%)          |
| <b>Ampere rating</b>                                 | 10Aac                  |
| <b>Operating temperature &amp; relative humidity</b> | 0°C~50°C Max. 80% R.H  |
| <b>Weight</b>  | Approx. 196g           |
| <b>Dimensions (mm)</b>                               | 160(L) x 57(W) x 42(D) |

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.